



ATO Request For Quote Form



Duty Cycle	Continuous	Intermittent	Use Once														
Working Pressure Bar/PSI											Customer						
Pressure Relief Valve	YES	NO											Name				
Relief Valve Setting?											Signature						
Flow- LPM																	
Pump Displacement	GP1	1.1cc	1.3cc	1.6cc	2.1cc	2.7cc	3.2cc	3.7cc	4.2cc	4.8cc	5.8cc	8.0cc					
	GP2	4cc	6cc	8cc	10cc	12cc	14cc	16cc	20cc	25cc							
	GP3	20cc	26cc	33cc	39cc	46cc	55cc	63cc									
Motor	AC	240volt		415volt		AIR			DC		ENGINE						
		2P	4P	6P	8P				12V	24V	PETROL	DIESEL					
Tank Capacity-LTR	40	50	75	130	200	300	400										
Return Filtration	Yes	No	Micron		5um	10um	25um	Clogging Indicator		YES	NO						
Pressure Gauge	Yes	No	Test Point		No	Yes											
Manifold	CT3	P & T with Relief					Series										
	CT5	Bulkhead Only					Paralell										
Directional Control Valves		A51												Z11			
		C51											Other				
		R11															
		C11															
		H11															
		Y11															
Control Voltage	12VDC	24VDC	24VAC	115VAC	240VAC												
Options	Pendant		Other Options														
	Wiring Loom																
	Power Lead																

Specification Selection Sheet

PT Hydraulics Australia Pty Ltd
 19 Ricketts Road
 Mount Waverley, VIC, 3149
 Tel: 03 9562 8800
 Fax: 03 9562 8080
www.pthydraulics.com.au
sales@pthydraulics.com.au