

SC 150

Technical Data

| | |
|--------------------------|--|
| Cutting forces up to | 43,160 lbs / 192 kN |
| Round stock up to dia. * | 0.8 in. / 22 mm |
| Spreading force up to | 25,400 lbs / 113 kN |
| Spreading distance | 10.5 in. / 265 mm |
| Oil requirement | 1.5 cu.in. / 25 cm ³ |
| Dimensions: l x w x h | 24.9 x 6.7 x 5.7 in. 632 x 171 x 145 mm |
| Weight | 22.7 lbs / 10.3 kg |

* According to EN 13204

Useful Accessories

| | | |
|-----------|--------|------------------|
| Blade Arm | Weight | 3.3 lbs / 1.5 kg |
|-----------|--------|------------------|



Power Units

P 600 OB
 GO-3T / DO-1R
 P 620 Series
 P 640 Series
 P 640 TRIMO



LUKAS Hydraulik GmbH - A Unit of IDEX Corporation
 Postfach 2560 · 91013 Erlangen · Weinstraße 39 · 91058 Erlangen · Germany
 Fon: +49 (0)9131/698 0 · Fax: +49 (0)9131/698 394
 lukas.info@idexcorp.com · www.lukas.de

LUKAS
Passion makes the difference!