

SC 350

Technical Data

Cutting force up to	85,430 lbs / 380 kN
Round steel up to dia. *	1.2 in. / 30 mm
Spreading force up to	25,400 lbs / 113 kN
Spreading distance	14.1 in. / 360 mm
Pulling force up to	10,228 lbs / 45.5 kN
Pulling distance	15 in. / 381 mm
Oil requirement	4 cu.in. / 66 cm ³
Dimensions: l x w x h	30.3 x 7.8 x 6.4 in. 770 x 199 x 163 mm
Weight	30.6 lbs / 13.9 kg

* According to EN 13204

Power Units

P 600 OB
GO-3T / DO-1R
P 620 Series
P 640 Series
P 640 TRIMO

Useful Accessories

Blade Arm	Weight	5 lbs / 2.3 kg
-----------	--------	----------------



Adjustable Handle



Chain Set KSV 8	Weight	19.6 lbs / 8.9 kg
-----------------	--------	-------------------



LUKAS Hydraulik GmbH · A Unit of IDEX Corporation
Postfach 2560 · 91013 Erlangen · Weinstraße 39 · 91058 Erlangen · Germany
Fon: +49 (0)9131/698 0 · Fax: +49 (0)9131/698 394
lukas.info@idexcorp.com · www.lukas.de

LUKAS

Passion makes the difference!