



# Fi-Serie

## Technical Data

### Cutter LS 330 Fi

Cutting force up to	114,500 lbs / 510 kN
Round steel material up to dia*	1.3 in. / 33 mm
Blade opening	9 in. / 228 mm
Oil requirement	6 cu.in. / 98 cm <sup>3</sup>
Dimensions: l x w x h	28.9 x 8.3 x 7.7 in.
	733 x 210 x 195 mm
Weight	39 lbs / 17.6 kg

### Combistool LKS 35 Fi

Cutting force up to	94,000 lbs / 418 kN
Round steel material up to dia*	1.2 in. / 30 mm
Spreading force up to	25,400 lbs / 113 kN
Spreading distance	14.2 in. / 360 mm
Oil requirement	4.2 cu.in. / 68 cm <sup>3</sup>
Dimensions: l x w x h	30 x 8.3 x 7.7 in.
	762 x 210 x 195 mm
Weight	37.5 lbs / 17 kg

\* According to EN 13204

## Power Units

- P 600 OB
- GO-3T / DO-1R
- P 640 Series
- P 640 TRIMO

## Useful Accessories

Cutter Blade for LS 330 Fi	Weight	6.8 lbs / 3.1 kg
----------------------------	--------	------------------



Blade Arm for LKS 35 Fi	Weight	5 lbs / 2.3 kg
-------------------------	--------	----------------



LS 330 Fi

LKS 35 Fi

LUKAS Hydraulik GmbH · A Unit of IDEX Corporation  
 Postfach 2560 · 91013 Erlangen · Weinstraße 39 · 91058 Erlangen · Germany  
 Fon: +49 (0)9131/698 0 · Fax: +49 (0)9131/698 394  
 lukas.info@idexcorp.com · www.lukas.de

**LUKAS**  
*Passion makes the difference!*