



# SP 310

## Technical Data


Spreading force up to	57,550 lbs / 256 kN
Spreading distance	28.3 in. / 720 mm
Squeezing force (with squeezing attachment) up to	27,430 lbs / 122 kN
Pulling distance up to	24.5 in. / 622 mm
Pulling force up to	11,500 lbs / 51 kN
Oil requirement	14.8 cu.in. / 243 cm <sup>3</sup>
Dimensions: l x w x h	31.1 x 11.8 x 7 in. 790 x 300 x 180 mm
Weight	43.2 lbs / 19.6 kg

## Power Units

P 600 OB  
 GO-3T / DO-1R  
 P 620 Series  
 P 640 Series  
 P 640 TRIMO

## Useful Accessories

Chain Set KSV 11 Weight 29.3 lbs / 13.3 kg



Quick-adjust Chain Set KSS 20 Weight 28.7 lbs / 13.0 kg



Spreader Tip Weight 2.4 lbs / 1.1 kg



Squeezing Attachment Weight 2.6 lbs / 1.2 kg



**LUKAS Hydraulik GmbH - A Unit of IDEX Corporation**  
 Postfach 2560 · 91013 Erlangen · Weinstraße 39 · 91058 Erlangen · Germany  
 Fon: +49 (0)9131/698 0 · Fax: +49 (0)9131/698 394  
 lukas.info@idexcorp.com · www.lukas.de

**LUKAS**  
*Passion makes the difference!*