

SP 510

Technical Data


Spreading force up to	51,700 lbs / 230 kN
Spreading distance	31.5 in. / 800 mm
Squeezing force (at spreader tip) up to	15.800 lbs / 70.4 kN
Pulling distance up to	26.2 in. / 665 mm
Pulling force up to	13,000 lbs / 58 kN
Oil requirement	25.9 cu.in./ 425 cm ³
Dimensions: l x w x h	35.4 x 13.5 x 8.5 in. 900 x 344 x 215 mm
Weight	55 lbs / 24.9 kg

Power Units

P 600 OB
 GO-3T / DO-1R
 P 620 Series
 P 640 Series
 P 640 TRIMO

Useful Accessories

Chain Set KSV 11 Weight 29.3 lbs / 13.3 kg



Quick-adjust Chain Set KSS 20 Weight 28.6 lbs / 13.0 kg



Spreader Tip Weight 2.4 lbs / 1.1 kg



LUKAS Hydraulik GmbH - A Unit of IDEX Corporation
 Postfach 2560 · 91013 Erlangen · Weinstraße 39 · 91058 Erlangen · Germany
 Fon: +49 (0)9131/698 0 · Fax: +49 (0)9131/698 394
 lukas.info@idexcorp.com · www.lukas.de

LUKAS
Passion makes the difference!