


SP 512

Technical Data

Spreading force up to	121,400 lbs / 540 kN
Spreading distance	24 in. / 610 mm
Squeezing force up to (at spreader tip)	28,700 lbs / 128 kN
Pulling distance up to	17.2 in. / 437 mm
Pulling force up to	22,200 lbs / 99 kN
Oil requirement	20.8 cu.in./ 341 cm ³
Dimensions: l x w x h	31.1 x 15 x 8.5 in. 790 x 380 x 216 mm
Weight	57.1 lbs / 25.9 kg

Useful Accessories

Chain Set KSV 13/100	Weight	54 lbs / 24.5 kg
----------------------	--------	------------------



Spreader Tip	Weight	3.5 lbs / 1.6 kg
--------------	--------	------------------



Power Units

P 600 OB
 GO-3T / DO-1R
 P 620 Series
 P 640 Series
 P 640 TRIMO



LUKAS Hydraulik GmbH · A Unit of IDEX Corporation
 Postfach 2560 · 91013 Erlangen · Weinstraße 39 · 91058 Erlangen · Germany
 Fon: +49 (0)9131/698 0 · Fax: +49 (0)9131/698 394
 lukas.info@idexcorp.com · www.lukas.de

LUKAS
Passion makes the difference!